



Tork Extra Starke Reinigungstücher (Weiß)



Artikel	530150
Länge entfaltet	32 cm
System	W8 – Small Pack
Breite entfaltet	38.5 cm
Länge gefaltet	16 cm
Breite gefaltet	19.5 cm
Lagen	1
Bedruckt	No
Farbe	Weiß

Diese extra starken, saugfähigen und vielseitig einsetzbaren Reinigungstücher sind für den Einsatz mit Lösungsmitteln geeignet. Sie schützen Ihre Hände vor Hitze und scharfen Metallteilen. Mit exelCLEAN™-Effekt für professionelle Reinigungsergebnisse.

- exelCLEAN™ für bessere Reinigungseffizienz
- Mehrzweck Tücher – für unterschiedlichste Reinigungsarbeiten geeignet
- Gute Aufnahme von Öl und Wasser
- Stark genug für kräftiges Scheuern
- Zertifiziert für den Kontakt mit Lebensmitteln

Transportdaten			
	Verbrauchseinheit	Transporteinheit	Palette
EAN	7322540238280	7322540238297	7322540239164
Stücke	45	360	21600
Verbrauchseinheit	-	8	480
Höhe	89 mm	182 mm	1970 mm
Breite	160 mm	400 mm	800 mm
Länge	195 mm	400 mm	1200 mm
Menge	2.8 dm ³	29.1 dm ³	1.7 m ³
Nettogewicht	444 g	3.5 kg	212.89 kg
Bruttogewicht	450 g	4.2 kg	251.76 kg
Verpackungsmaterial	Plastic	Carton	-

Umweltinformationen	
Content	Chemical pulp Polypropene Polyester Chemicals
Material	Chemical pulp Chemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities. There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free). ECF is based on oxygene, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone. ECF is used in this product. Polypropene Polypropene fibre is produced from polypropene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length. Polyester Polyester fibre is produced from terephthalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length. The fibre used contains black pigments. Chemicals Both functional and process chemicals are used. The functional chemical used is wetstrength agent. The wetstrength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre. Process chemical used is a surfactant.
Production	The material is produced at Suameer mill, NL, certified according to ISO 9001:2000, ISO 14001 and EMAS. Product converted externally in DE.
Destruction	This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destructed. The product itself is suitable for incineration. Contact local authorities before destruction.

Alternative Produkte



Produktzertifikate



Kontakt

SCA Hygiene Products AFH Sales GmbH
Sandhofer Straße 176
68305 Mannheim

Tel.: +49 (0)621/778 4700
Mo-Do 8:00-16:00 Uhr | Fr 8:00-15:00 Uhr

Fax: +49 (0)621/778 13 4700
E-Mail: torkmaster@sca.com